

Content-based fMRI activation maps retrieval





Alba G. Seco de Herrera, L. Rodney Long, Sameer Antani

Lister Hill National Center for Biomedical Communications, National Library of Medicine, Bethesda, USA

Summary

- 1. Statistical analysis of fMRI data is used to locate brain activity and generate brain activation maps
- 2. CB-fMRI activation maps retrieval return activation maps that have similar activation patterns to the given one

Introduction

- Functional Magnetic Resonance Imaging (fMRI)
 - To study brain response to tasks
 - Non-invasive
 - Detect signal changes in areas of the brain where neuronal activity is varying
 - Brain activation statistical maps show brain activity
- Content-based (CB-) fMRI retrieval
- To manage neuroimaging data sharing
- To retrieve studies relevant to a «query» brain activation map




Image collection


- 8 experiments: morality, recall, romantic, visual, study, house, recallFree, auditory
- 359 subjects in total
- 10 Probabilistic Independent Component Analysis (PICA) components per subject

Conclusions


- This poster presents a novel method for fMRI brain activation map retrieval
- It is **difficult** to **assess** when a fMRI brain activation map is relevant for a given query, therefore the evaluation method has limitations
- The results are promising but there is a big difference between experiments


Methods

- Feature extraction
- Map layout descriptor
- Whole–brain ROI–wise



- Similarity comparison
- Euclidean distance
- Histogram intersection (HI)





Acknowledgments This research was supported in part by the Intramural Research Program of the National Institutes of Health (NIH), National Library of Medicine (NLM), and Lister Hill National Center for Biomedical Communications (LHNCBC).